

关于卧龙

1984

30


“ ” 5 “ ”

卧龙集团

产品介绍

1Ph 230VAC 50/60Hz				
0.15kW-0.3kW				
≥ 0.6				
-25	60			-40
-30~40				
0-10V RS485				
B3	B30	B14		
IP20	IP44	IP55	IP66	
C3-H	C4-H			
UL	CE	CCC		

		[V]		[Hz]	[kW]	[r/min]					[A]		[%]
EM4210A15***	1~220-240	50/60	0.15	720/960/1000/1050/1200				200~1200	1.4	80%			
EM4210A13***	1~220-240	50/60	0.25	720/960/1000/1050/1200				200~1200	2.1	81%			
EM4210A12***	1~220-240	50/60	0.37	960/1000/1050/1200				200~1200	2.8	82%			
EM4210B15***	1~220-240	50/60	0.15	1350/1500/1800/2200				200~2200	1.5	81%			
EM4210B13***	1~220-240	50/60	0.25	1350/1500/1800/2200				200~2200	2.2	82%			
EM4210B12***	1~220-240	50/60	0.3	1350/1500/1800/2200				200~2200	3	83%			
	A	B	C	D	E	H	K	L	AB	AC	BB	EB	HD
42	112	90	45	12.7/15/17/20	/	71	8.5	244	135	102.5	110	/	135



3Ph 380~480VAC 50/60Hz				
1.1	2.2kW			
≥ 0.9				
-25	~55	-40		
-30~40				
0-10V RS485				
B3	B30	B14		
IP55	IP66			
C3-H	C4-H			
UL	CE			

		[V]	[Hz]	[kW]		[r/min]					[A]	[%]	
EM5610A32***		3~380-480V	50/60	1.1		720/960/1000/1050/1200			200~1200		2.4	86%	
EM5610A21***		3~380-480V	50/60	1.5		720/960/1000/1050/1200			200~1200		3.2	87%	
EM5610A31***		3~380-480V	50/60	2.2		960/1000/1050/1200			200~1200		4.5	88%	
EM5610B32***		3~380-480V	50/60	1.1		1350/1500/1800/2200			200~2200		2.4	88%	
EM5610B21***		3~380-480V	50/60	1.5		1350/1500/1800/2200			200~2200		3.2	89%	
EM5610B31***		3~380-480V	50/60	2.2		1350/1500/1800/2200			200~2200		4.5	90%	
	A	B	C	D	E	H	K	L	AB	AC	BB	EB	HD
56	140	100	/	20/24	/	90/100	11	/	180	138.5	130	/	141

3Ph 380~480VAC 50/60Hz		
1.5	3kW	
≥ 0.9		
-25	~55	-40
-30~40		
0-10V	RS485	
B30		
IP55	IP66	
C3-H	C4-H	
UL	CE	

	[V]	[Hz]	[kW]	[r/min]		[A]	[%]
EM13210A31***	3~380-480V	50/60	1.5	720/960/1000/1200	200~1200	3.0~2.4	89%
EM13210A31***	3~380-480V	50/60	1.8	720/960/1000/1200	200~1200	3.5~2.9	89%
EM13210A31***	3~380-480V	50/60	2.2	720/960/1000/1200	200~1200	4.3~3.5	90%
EM13210A72***	3~380-480V	50/60	2.6	960/1000/1200	200~1200	5.0~4.0	90%
EM13210A41***	3~380-480V	50/60	3.0	960/1000/1200	200~1200	5.8~4.5	90%
EM13210B31***	3~380-480V	50/60	1.5	1300/1450/1500/1800	200~1800	3.0~2.4	90%
EM13210B31***	3~380-480V	50/60	1.8	1300/1450/1500/1800	200~1800	3.5~2.9	90%
EM13210B31***	3~380-480V	50/60	2.2	1300/1450/1500/1800	200~1800	4.3~3.5	91%
EM13210B72***	3~380-480V	50/60	2.6	1300/1450/1500/1800	200~1800	5.0~4.0	91%
EM13210B41***	3~380-480V	50/60	3.0	1300/1450/1500/1800	200~1800	5.8~4.5	91%

